


Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Air Flow (CFM)	Initial Resistance (In. W.G.)	MERV	Media Area (Square Feet)
CS-904	24 X 24 X 4	23-3/8 X 23-3/8 X 3-3/4	2000	0.70	14	103
CS-912	20 X 25 X 4	19-3/8 X 24-3/8 X 3-3/4	1750	0.70	14	91
CS-915	20 X 24 X 4	19-3/8 X 23-3/8 X 3-3/4	1650	0.70	14	89
CS-913	20 X 20 X 4	19-3/8 X 19-3/8 X 3-3/4	1400	0.70	14	71
CS-911	18 X 24 X 4	17-3/8 X 23-3/8 X 3-3/4	1500	0.70	14	76
CS-910	16 X 25 X 4	15-3/8 X 24-3/8 X 3-3/4	1400	0.70	14	71
CS-909	16 X 20 X 4	15-3/8 X 19-3/8 X 3-3/4	1100	0.70	14	57
CS-903	12 X 24 X 4	11-3/8 X 23-3/8 X 3-3/4	1000	0.70	14	50
CS-804	24 X 24 X 4	23-3/8 X 23-3/8 X 3-3/4	2000	0.65	13	103
CS-812	20 X 25 X 4	19-3/8 X 24-3/8 X 3-3/4	1750	0.65	13	91
CS-815	20 X 24 X 4	19-3/8 X 23-3/8 X 3-3/4	1650	0.65	13	89
CS-813	20 X 20 X 4	19-3/8 X 19-3/8 X 3-3/4	1400	0.65	13	71
CS-811	18 X 24 X 4	17-3/8 X 23-3/8 X 3-3/4	1500	0.65	13	76
CS-810	16 X 25 X 4	15-3/8 X 24-3/8 X 3-3/4	1400	0.65	13	71
CS-809	16 X 20 X 4	15-3/8 X 19-3/8 X 3-3/4	1100	0.65	13	57
CS-803	12 X 24 X 4	11-3/8 X 23-3/8 X 3-3/4	1000	0.65	13	50
CS-604	24 X 24 X 4	23-3/8 X 23-3/8 X 3-3/4	2000	0.48	11	103
CS-612	20 X 25 X 4	19-3/8 X 24-3/8 X 3-3/4	1750	0.48	11	91
CS-615	20 X 24 X 4	19-3/8 X 23-3/8 X 3-3/4	1650	0.48	11	89
CS-613	20 X 20 X 4	19-3/8 X 19-3/8 X 3-3/4	1400	0.48	11	71
CS-611	18 X 24 X 4	17-3/8 X 23-3/8 X 3-3/4	1500	0.48	11	76
CS-610	16 X 25 X 4	15-3/8 X 24-3/8 X 3-3/4	1400	0.48	11	71
CS-609	16 X 20 X 4	15-3/8 X 19-3/8 X 3-3/4	1100	0.48	11	57
CS-603	12 X 24 X 4	11-3/8 X 23-3/8 X 3-3/4	1000	0.48	11	50

STANDARD CONSTRUCTION

1. High Efficiency, Microglass Paper Media
2. Corrugated Aluminum Separators With Rolled Edges
3. 24 Gauge Aluminized Steel Cell Sides
4. Expanded Metal Grid on Both Sides

NOTES

1. Testing per ASHRAE 52.2-2012
Filters Tested at 492 FPM on 24x24x4 Nominal Size
2. Final Resistance: 1.5" W.G.
Recommended Not To Exceed 1.2" W.G Above 250 deg. F
3. Rated Velocity 4" Deep - 500 FPM
4. Classified per UL Standard 900 for Flammability
5. Maximum Operating Temperature: 750 deg. F
6. Optional High Temperature Gasket Available
U - Upstream Gasket (Ex: CS-904-U)
D - Downstream Gasket
UD- Both Sides
7. Special Sizes and Gasket Options are Available

 <p>100 River Ridge Circle Jeffersonville, IN 47130 P: 866-247-4827 F: 866-801-1809 www.clcair.com/airguard</p>	<p>TOLERANCES UNLESS OTHERWISE SPECIFIED</p> <p>FRACTIONAL - DECIMAL - ANGLES -</p>		<p>DRAWING NAME VARIFLOW COMPACT SERIES</p>	
	<p>CONTACT FACTORY TO VERIFY REVISION LEVEL</p>		<p>APPROVED BY <i>K. Quinn</i> SPECIFICATION NO. MKT-B-00149 PAGE 1 OF 1</p> <p>SCALE NONE DWG. SIZE A REVISION B REVISION DATE 05-25-16</p>	
<p>ALL DIMENSIONS IN INCHES</p>		<p><small>CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLCAIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.</small></p>		