



Model Number *	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Air Flow (CFM)	Initial Resistance (IN W.G.)			Media Area (Square Feet)
				90-95%	80-85%	60-65%	
VSC-FC_04	24 x 24 x 12	23-3/8 x 23-3/8 x 11-1/2	2000	.70	.60	.43	103
VSC-FC_12	20 x 25 x 12	19-3/8 x 24-3/8 x 11-1/2	1750	.70	.60	.43	88
VSC-FC_15	20 x 24 x 12	19-3/8 x 23-3/8 x 11-1/2	1650	.70	.60	.43	84
VSC-FC_13	20 x 20 x 12	19-3/8 x 19-3/8 x 11-1/2	1400	.70	.60	.43	69
VSC-FC_11	18 x 24 x 12	17-3/8 x 23-3/8 x 11-1/2	1500	.70	.60	.43	75
VSC-FC_10	16 x 25 x 12	15-3/8 x 24-3/8 x 11-1/2	1400	.70	.60	.43	69
VSC-FC_09	16 x 20 x 12	15-3/8 x 19-3/8 x 11-1/2	1100	.70	.60	.43	53
VSC-FC_03	12 x 24 x 12	11-3/8 x 23-3/8 x 11-1/2	1000	.70	.60	.43	47
VSC-FC_02	24 x 24 x 6	23-3/8 x 23-3/8 x 5-7/8	1000	.40	.38	.23	47
VSC-FC_08	20 x 25 x 6	19-3/8 x 24-3/8 x 5-7/8	875	.40	.38	.23	40
VSC-FC_16	20 x 24 x 6	19-3/8 x 23-3/8 x 5-7/8	825	.40	.38	.23	38
VSC-FC_14	20 x 20 x 6	19-3/8 x 19-3/8 x 5-7/8	700	.40	.38	.23	32
VSC-FC_07	18 x 24 x 6	17-3/8 x 23-3/8 x 5-7/8	750	.40	.38	.23	34
VSC-FC_06	16 x 25 x 6	15-3/8 x 24-3/8 x 5-7/8	700	.40	.38	.23	31
VSC-FC_05	16 x 20 x 6	15-3/8 x 19-3/8 x 5-7/8	550	.40	.38	.23	24
VSC-FC_01	12 x 24 x 6	11-3/8 x 23-3/8 x 5-7/8	500	.40	.38	.23	21

* - Insert Filter Efficiency Code (9=90-95%, 8=80-85%, 6=60-65%), Example VSC-FC-904 is 90-95%, 24x24x12 Nominal Size

STANDARD CONSTRUCTION

1. High Efficiency, Microglass Paper Media
2. Corrugated Aluminum Separators With Rolled Edges
3. Microglass Paper Wrap Around Media Pack
Latex Adhesive Sealant
4. 1/2" Particle Board Cell Sides
5. Header on Both Side: Single Piece U-Channel

NOTES

1. Average Efficiency, MERV (52.2)
90-95% ASHRAE 52.1-1992, MERV 14 ASHRAE 52.2-1999
80-85% ASHRAE 52.1-1992, MERV 13 ASHRAE 52.2-1999
60-65% ASHRAE 52.1-1992, MERV 11 ASHRAE 52.2-1999
2. Final Resistance: 1.5" W.G.
3. Rated Velocity 12" Deep - 500 FPM
4. Rated Velocity 6" Deep - 250 FPM
5. Class 2 Filter Per U.L. Standard 900
6. Maximum Operating Temperature: 200 deg. F
7. Optional Gasket Available
U - Upstream Gasket (Ex: VSC-FC-904-U)
D - Downstream Gasket
UD- Both Sides
8. Reverse Pleat Orientation Available
Add "-R" to Model Number (Ex: VSC-FC-904-R)
9. Special Sizes Available

AIRGUARD ONE SOURCE FOR AIR FILTRATION PRODUCTS
 P.O. Box 32578
 Louisville, KY 40232
 P: 502-969-2304
 F: 502-961-0930

CONTACT FACTORY TO
 VERIFY REVISION LEVEL

TOLERANCES
 UNLESS OTHERWISE SPECIFIED

- FRACTIONAL
- DECIMAL
- ANGLES

ALL DIMENSIONS IN INCHES

DRAWING NAME
VARIFLOW VSC-FC (WOOD DOUBLE HEADER)

APPROVED BY <i>K. [Signature]</i>	SPECIFICATION NO. MKT-B-00146	PAGE 1 OF 1
SCALE NONE	DWG SIZE A	REVISION B
		REVISION DATE 07-02-04

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY AIRGUARD. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.