



Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Airflow (CFM)	Initial Resistance (In W.G.)	Media Area (Square Feet)
XP-STD1-117	10 X 20 X 1	9-1/2 X 19-1/2 X 3/4	415	0.15	2.3
XP-STD1-124	10 X 24 X 1	9-3/8 X 23-3/8 X 3/4	500	0.15	2.8
XP-STD1-122	12 X 12 X 1	11-3/4 X 11-3/4 X 3/4	300	0.15	1.8
XP-STD1-120	12 X 20 X 1	11-1/2 X 19-1/2 X 3/4	500	0.15	2.8
XP-STD1-110	12 X 24 X 1	11-3/8 X 23-3/8 X 3/4	600	0.15	3.4
XP-STD1-133	14 X 14 X 1	13-3/4 X 13-3/4 X 3/4	410	0.15	2.4
XP-STD1-139	14 X 20 X 1	13-1/2 X 19-1/2 X 3/4	585	0.15	3.3
XP-STD1-159	14 X 24 X 1	13-3/8 X 23-3/8 X 3/4	700	0.15	4.0
XP-STD1-141	14 X 25 X 1	13-1/2 X 24-1/2 X 3/4	730	0.15	4.2
XP-STD1-137	14 X 30 X 1	13-3/4 X 29-3/4 X 3/4	875	0.15	5.2
XP-STD1-145	15 X 20 X 1	14-1/2 X 19-1/2 X 3/4	625	0.15	3.6
XP-STD1-143	16 X 16 X 1	15-1/2 X 15-1/2 X 3/4	530	0.15	3.0
XP-STD1-101	16 X 20 X 1	15-1/2 X 19-1/2 X 3/4	665	0.15	3.8
XP-STD1-116	16 X 24 X 1	15-3/8 X 23-3/8 X 3/4	800	0.15	4.6
XP-STD1-102	16 X 25 X 1	15-1/2 X 24-1/2 X 3/4	835	0.15	4.8
XP-STD1-146	16 X 30 X 1	15-3/4 X 29-3/4 X 3/4	1000	0.15	6.0
XP-STD1-163	18 X 18 X 1	17-3/4 X 17-3/4 X 3/4	675	0.15	4.1
XP-STD1-180	18 X 20 X 1	17-3/8 X 19-1/2 X 3/4	750	0.15	4.3
XP-STD1-112	18 X 24 X 1	17-3/8 X 23-3/8 X 3/4	900	0.15	5.2
XP-STD1-185	18 X 25 X 1	17-1/2 X 24-1/2 X 3/4	936	0.15	5.4
XP-STD1-103	20 X 20 X 1	19-1/2 X 19-1/2 X 3/4	830	0.15	4.8
XP-STD1-166	20 X 22 X 1	19-3/4 X 21-3/4 X 3/4	915	0.15	5.5
XP-STD1-111	20 X 24 X 1	19-3/8 X 23-3/8 X 3/4	1000	0.15	5.9
XP-STD1-104	20 X 25 X 1	19-1/2 X 24-1/2 X 3/4	1040	0.15	6.1
XP-STD1-132	20 X 30 X 1*	19-1/2 X 29-1/2 X 3/4	1250	0.15	7.3
XP-STD1-105	24 X 24 X 1	23-3/8 X 23-3/8 X 3/4	1200	0.15	7.0
XP-STD1-153	24 X 30 X 1	23-3/4 X 29-3/4 X 3/4	1500	0.15	9.1
XP-STD1-125	25 X 25 X 1	24-1/2 X 24-1/2 X 3/4	1300	0.15	7.7

\* Reverse Pleat

**STANDARD CONSTRUCTION**

1. 100% Synthetic, Self-Supporting Media
2. 12.0 Pleats per Foot
3. (3) Pleat Stabilizer Straps, Upstream Side
4. Media Pack Support Grid, Downstream Side
5. Moisture Resistant Beverage Board Frame

**NOTES**

1. Average Efficiency: MERV 8 ASHRAE 52.2-2012  
Tested at 295 FPM on 24x24x1 nominal size.
2. MERV-A 8-A ASHRAE 52.2-2012 Appendix J
3. Final Resistance: 1.0" W.G.
4. Rated Velocity: 300 FPM
5. Classified Per UL Standard 900 For Flammability
6. Maximum Operating Temperature: 150 deg. F



100 River Ridge Circle  
Jeffersonville, IN 47130  
P: 866-247-4827  
F: 866-801-1809  
www.dlcair.com/airguard

CONTACT FACTORY TO  
VERIFY REVISION LEVEL

**TOLERANCES**  
UNLESS OTHERWISE SPECIFIED

FRACTIONAL -  
DECIMAL -  
ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

XTREME-PLUS STANDARD CAPACITY SSP 1" DEPTH

APPROVED BY

*K. Quinn*

SPECIFICATION NO.

MKT-B-00606

PAGE 1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

H

REVISION DATE

05-18-15

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLCAIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.