

Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Airflow (CFM)	Initial Resistance (In W.G.)	Media Area (Square Feet)
XP-STD2-217	10 X 20 X 2	9-1/2 X 19-1/2 X 1-3/4	700	0.22	4.0
XP-STD2-220	12 X 20 X 2	11-1/2 X 19-1/2 X 1-3/4	840	0.22	4.8
XP-STD2-210	12 X 24 X 2	11-3/8 X 23-3/8 X 1-3/4	1000	0.22	5.7
XP-STD2-239	14 X 20 X 2	13-1/2 X 19-1/2 X 1-3/4	980	0.22	5.5
XP-STD2-241	14 X 25 X 2	13-1/2 X 24-1/2 X 1-3/4	1220	0.22	6.9
XP-STD2-245	15 X 20 X 2	14-1/2 X 19-1/2 X 1-3/4	1050	0.22	6.0
XP-STD2-243	16 X 16 X 2	15-3/4 X 15-3/4 X 1-3/4	890	0.22	5.3
XP-STD2-201	16 X 20 X 2	15-1/2 X 19-1/2 X 1-3/4	1120	0.22	6.5
XP-STD2-216	16 X 24 X 2	15-3/8 X 23-3/8 X 1-3/4	1340	0.22	7.5
XP-STD2-202	16 X 25 X 2	15-1/2 X 24-1/2 X 1-3/4	1400	0.22	8.2
XP-STD2-263	18 X 18 X 2	17-3/4 X 17-3/4 X 1-3/4	1125	0.22	6.6
XP-STD2-280	18 X 20 X 2	17-1/2 X 19-2/3 X 1-3/4	1250	0.22	7.3
XP-STD2-212	18 X 24 X 2	17-3/8 X 23-3/8 X 1-3/4	1500	0.22	8.7
XP-STD2-285	18 X 25 X 2	17-1/2 X 24-1/2 X 1-3/4	1570	0.22	9.2
XP-STD2-203	20 X 20 X 2	19-1/2 X 19-1/2 X 1-3/4	1400	0.22	8.0
XP-STD2-211	20 X 24 X 2	19-3/8 X 23-3/8 X 1-3/4	1670	0.22	9.6
XP-STD2-204	20 X 25 X 2	19-1/2 X 24-1/2 X 1-3/4	1750	0.22	10.1
XP-STD2-232	20 X 30 X 2*	19-1/2 X 29-1/2 X 1-3/4	2085	0.22	12.2
XP-STD2-205	24 X 24 X 2	23-3/8 X 23-3/8 X 1-3/4	2000	0.22	11.8
XP-STD2-225	25 X 25 X 2	24-1/2 X 24-1/2 X 1-3/4	2170	0.22	12.9


\* Reverse Pleat

**STANDARD CONSTRUCTION**

1. 100% Synthetic, Self-Supporting Media
2. 10.2 Pleats per Foot
3. (3) Pleat Stabilizer Straps, Upstream Side
4. Media Pack Support Grid, Downstream Side
5. Moisture Resistant Beverage Board Frame

**NOTES**

1. Average Efficiency: MERV 8 ASHRAE 52.2-2012  
Tested at 492 FPM on 24x24x2 nominal size.
2. MERV-A 8-A ASHRAE 52.2-2012 Appendix J
3. Final Resistance: 1.0" W.G.
4. Rated Velocity: 500 FPM
5. Classified Per UL Standard 900 For Flammability
6. Maximum Operating Temperature: 150 deg. F

 <p>100 River Ridge Circle Jeffersonville, IN 47130 P: 866-247-4827 F: 866-801-1809 www.dlcair.com/airguard</p>	<p><b>TOLERANCES</b> UNLESS OTHERWISE SPECIFIED</p> <p>FRACTIONAL - DECIMAL - ANGLES -</p>	DRAWING NAME <b>XTREME-PLUS STANDARD CAPACITY SSP 2" DEPTH</b>			
		APPROVED BY <i>K. Quinn</i>	SPECIFICATION NO. <b>MKT-B-00607</b>	PAGE <b>1 OF 1</b>	
<p><b>CONTACT FACTORY TO VERIFY REVISION LEVEL</b></p>	<p>ALL DIMENSIONS IN INCHES</p>	SCALE <b>NONE</b>	DWG. SIZE <b>A</b>	REVISION <b>H</b>	REVISION DATE <b>05-19-15</b>
		<p><small>CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.</small></p>			